

上升下降混合機 & 升降翻轉裝置

BIN BLENDER & TILTING DEVICE



原理介紹 +

- 升降：以油壓缸動作，提升料桶，可自動定位。
- 翻轉：以減速機轉動，可旋轉360°自動定位。

功能 +

- 粉末與顆粒的混合。將不同種類的粉末原料以及完成的顆粒添加潤滑劑、黏合劑、香料等之混合，達到所需之均勻度。

適用產業 +

藥品、食品、化工、飼料、農產品。

特點 +

- 以紅外線感測器包圍安全區域。
- 線控操作，操作簡單，清洗容易。
- 密閉操作，減少粉塵。
- 可與整粒機做連結，連結下料節省人力，減少粉塵。
- 可以加選自動給料裝置。

+



已申請專利
Patented

THEORY +

- **Lift:** Drums lifted by hydraulic cylinder. Drums can be positioned automatically.
- **Flip:** Can be rotated by reducer, and can be 360° positioned automatically.

FUNCTION +

- Powder and granule mixing. Mix different kind of powder materials and granules with lubricant, binder or essence oil of flavor to required uniformity.

APPLICATION +

Pharmaceutical, Cosmetic, Agriculture, Health Food or Bio-tech Products

FEATURES +

- Safety area surrounded by infrared ray
- Operation by wire, easy to use and clean
- Closed operation, reduce dust
- Extra automatic feeding device for optional choice

規格表 | SPECIFICATION

型號 Model	全容積 Full Volume (L)	工作容積 Work Volume (L) (40%-60%)	產能/批次 Capacity/Batch (Kgs)(B/D:0.5)
YS-LBIN-100	100	40-60	20-30
YS-LBIN-300	300	120-180	40-60
YS-LBIN-600	600	240-360	120-180
YS-LBIN-1000	1000	400-600	200-300
YS-LBIN-1200	1200	480-720	240-360
YS-LBIN-1400	1400	560-840	280-420

*Customized machinery for varied capacity. *Capacity based on B/D:0.5